

AA-229H

AA-229H is a Methacrylic copolymer emulsion designed for use as a binder in water based flat paints and both interior and exterior coatings.

AA-229H is **Alkyl Phenol free**.

AA- 229H Typical Properties :

Solids Content	50±1%
Viscosity at 25° C LVT 3/30	1000-2500 cps
PH	7.5-9.0
Particle Size	0.1-0.2 microns
Specific Gravity at 25° C	1.04
Surfactant Type	Anionic
Freeze/Thaw Stability	Unstable
Minimum Film Formation Temperature	+12°C
Tg	+20°C

Film Properties :

AA-229H forms a colorless, glossy, soft, flexible film. It has high tensile strength and wet abrasion resistance. Capable of superior elongation of 500% until break.

Application :

Can be used in a wide range of emulsion paint formulations, for flat interior and exterior paints with excellent water abrasion resistance.

AA-229H has a medium viscosity, fine particle size, recommended for self-textured finishes providing good color, stain resistance and flexibility.

Packaging :

200-kilo lacquer lined metal drums with polyethylene inner liner, 1-ton polyethylene container.

Storage :

AA-229H can be stored in original containers it is supplied in. Store in shade and protect from freezing.

Further Information about safe handling of this product can be found in the publication, "B.G. Polymers Safety Data Sheet".

All the information included in this data sheet is correct and is presented to the best of our knowledge and experience without warranty. Information on the use of our products should be adapted to local conditions. B.G Technologies cannot accept responsibility or liability for any damage, loss or patent infringements from the use of this information.